

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

Product name : HYDROFAN CLEARCOAT HARDENER
Product code : LOHH0960
Use of the Substance/Preparation : Poliisocyanic compound - professional use
Company : Lechler SpA
Via Cecilio 17
22100 Como
Telephone : +39031586111
Telefax : +39031586206
E-mail address : safety@lechler.it

In order to get more information and in case of emergencies please address to Lechler Group Security Office.

: Tel. +39-031-586301
Fax +39-031-586299

2. HAZARDS IDENTIFICATION



Hazardous components which must be listed on the label:

- Polysocyanate HDI Derivative

R-phrases :

Flammable.

Irritating to eyes.

May cause sensitization by inhalation and skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases :

Do not breathe spray.

Avoid contact with skin.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable gloves.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Special labelling of certain preparations :

Contains isocyanates. See information supplied by the manufacturer.

Revision Date 15.10.2010
Version 1

Print Date 19/10/2010

3. COMPOSITION/INFORMATION ON INGREDIENTS**Chemical nature** : Poliisocyanic compound - professional use**Hazardous components** :

Components	CAS-No.	EC-No.	Symbol(s)	R-phrase(s)	Concentration [%]
2-Methoxy-1-Methylethyl Acetate	108-65-6	607-195-00-7	Xi	R10, R36	>= 30 - < 50
Hexamethylene-di-Isocyanate	822-06-0	615-011-00-1	T	R23, R36/37/38, R42/43	>= 0,1 - < 0,2
Polysocyanate HDI Derivative	28182-81-2		Xi	R42/43, R52/53	>= 50 - <= 100

4. FIRST AID MEASURES**General advice** : When symptoms persist or in all cases of doubt seek medical advice.
Never give anything by mouth to an unconscious person.**Inhalation** : Remove to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious place in recovery position and seek medical advice.**In case of skin contact** : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Do NOT use solvents or thinners.
Put shower on working place**In case of eye contact** : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Seek medical advice.
Put eye-washer on working place
Remove contact lenses.**If swallowed** : If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting.
Keep at rest.**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media** : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Keep containers and surroundings cool with water spray.

Revision Date 15.10.2010
Version 1

Print Date 19/10/2010

- Extinguishing media which shall not be used for safety reasons : Do NOT use water jet.
- Specific hazards during fire fighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.
Cool closed containers exposed to fire with water spray.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Solvent vapours are heavier than air and may spread along floors.
Ensure adequate ventilation.
Use personal protective equipment.
Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ventilate the area.
- Environmental precautions : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Clean with detergents. Avoid solvents.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/ concentrated (d:0,880) ammonia solution (5 parts). A non flammable alternative is sodium carbonate (5 parts)/ water (95 parts).
Pick up and transfer to properly labelled containers.
Clean contaminated surface thoroughly.
Dam up.
Soak up with inert absorbent material and dispose of as hazardous waste.
- Additional advice : Refer to section 15 for specific national regulation.

Revision Date 15.10.2010
Version 1

Print Date 19/10/2010

7. HANDLING AND STORAGE**Handling**

- Safe handling advice : Avoid exceeding of the given occupational exposure limits (see section 8).
Use only in area provided with appropriate exhaust ventilation.
Avoid contact with skin, eyes and clothing.
Smoking, eating and drinking should be prohibited in the application area.
Avoid inhalation of vapour or mist.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.
Thoroughly mix before using
After using, store in a well-sealed container
- Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
When transferring from one container to another apply earthing measures and use conductive hose material.
No sparking tools should be used.
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
No smoking.

Storage

- Requirements for storage areas and containers : Observe label precautions.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.
Electrical installations / working materials must comply with the technological safety standards.
Store in accordance with the particular national regulations.
- Advice on common storage : Keep away from oxidising agents, strongly acid or alkaline materials, as well as of amines, alcohols and water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value [mg/m ³]	Value [ppm]	Basis
2-Methoxy-1-Methylethyl Acetate	108-65-6	275,00	50,00	

Personal protective equipment

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.

Revision Date 15.10.2010
Version 1

Print Date 19/10/2010

This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Wear a positive-pressure supplied-air respirator.

- Hand protection** : For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact. Wash your hands and put on barrier creams. Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Eye protection** : Chemical resistant goggles must be worn.
- Skin and body protection** : Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Personnel should wear protective clothing. Workers should wear antistatic footwear.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form** : liquid
- Flash point** : > 23 - 55 °C
- Density** : 1,05 g/cm³
- Viscosity** : ≤ 60 s
Transversale section: 6 mm
Method: 2431 '84 (ISO 6)
- Solids by weight** : 52 %
- Volatile organic compounds (VOC) content** : 48 %

10. STABILITY AND REACTIVITY

- Conditions to avoid** : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

Revision Date 15.10.2010
Version 1

Print Date 19/10/2010

Hazardous reactions : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Avoid moisture.
Amines and alcohols cause exothermic reactions.
Preparation reacts slowly with water resulting in evolution of CO₂.
Evolution of CO₂ in closed containers causes overpressure and produces a risk of bursting.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.
Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system.
Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
Inhalation of airborne droplets may cause irritation of the respiratory tract.

Acute toxicity (other routes of administration) : Isocyanates may cause acute irritation and/or sensitisation of the respiratory system leading to tightness of the chest, wheeziness and an asthmatic condition.

Skin irritation : Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin.
The product may be absorbed through the skin.

Note : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

12. ECOLOGICAL INFORMATION

Further information on ecology : The product contains dangerous substances for the environment (see chapter n° 2), The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

13. DISPOSAL CONSIDERATIONS

Product : The product should not be allowed to enter drains, water courses or the soil.
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Must be incinerated.

Contaminated packaging : Can be used after re-conditioning.
Empty remaining contents.
It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

Revision Date 15.10.2010
Version 1

Print Date 19/10/2010

European Waste Catalogue : waste isocyanates

packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

ADR	: UN-Number	1263
	Class	3
	Packing instruction (LQ)	F1
	Packaging group	III
	Description of the goods	PAINT RELATED MATERIAL
IMDG	: UN-Number	1263
	Class	3
	EmS	F - E, S - E
	Packaging group	III
	Description of the goods	PAINT RELATED MATERIAL
IATA	: UN-Number	1263
	Class	3
	Packaging group	III
	Description of the goods	Paint related material

15. REGULATORY INFORMATION

Hazardous components which must be listed on the label:

- Polysocyanate HDI Derivative

Symbol(s)	: Xn	Harmful
R-phrase(s)	: R10	Flammable.
	R36	Irritating to eyes.
	R42/43	May cause sensitization by inhalation and skin contact.
	R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S-phrase(s)	: S23	Do not breathe spray.
	S24	Avoid contact with skin.
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S37	Wear suitable gloves.
	S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Special labelling of certain preparations	:	
Special labelling of certain	:	Contains isocyanates. See information supplied by the manufacturer.

Revision Date 15.10.2010
Version 1

Print Date 19/10/2010

preparations

National legislationGermany

Risk classification according to BetrSichV (Germany) : Exempt
Water contaminating class (Germany) : WGK 1 slightly water endangering

16. OTHER INFORMATION**Further information**

2-Methoxy-1-Methylethyl Acetate	R10 R36	Flammable. Irritating to eyes.
Hexamethylene-di-Isocyanate	R23 R36/37/38 R42/43	Toxic by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact.
Polysocyanate HDI Derivative	R42/43 R52/53	May cause sensitization by inhalation and skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Version: 1.4

Revision Date 15.10.2010

This safety datasheet has been prepared according to European Union legislation.