Printing date: 01/08/2016 Revision: 01/08/2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

For professional use only

- · 1.1 Product identifier For professional use only
- · Trade name: 2K RS Non-Isocyanate Hardener
- · Article number: T368
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture Surface Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

TECHNICO SURFACE COATINGS LIMITED UNIT 14 BLYTHE PARK, SANDON ROAD CRESSWELL, STOKE ON TRENT STAFFORDSHIRE. ST11 9RD.

TEL: +44 (0)1782 397400 EMAIL: <u>info@technicouk.com</u>

- · Further information obtainable from: Technico Office
- · 1.4 Emergency telephone number: +44 (0)1782 397400 (Business hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K RS Non-Isocyanate Hardener

(Contd. of page 1)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1330-20-7	Xylene (mix)	25-50%
EINECS: 215-535-7	□ Flam. Liq. 3, H226; □ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 100-41-4	ethylbenzene	2.5-10%
EINECS: 202-849-4	► Flam. Liq. 2, H225; ~ Acute Tox. 4, H332	
CAS: 123-86-4	Butyl ethanoate	2.5-10%
EINECS: 204-658-1	№ Flam. Liq. 3, H226; № STOT SE 3, H336	
CAS: 71-36-3	butanol	2.5-10%
EINECS: 200-751-6	☐ Flam. Liq. 3, H226; ~ Eye Dam. 1, H318; ~ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K RS Non-Isocyanate Hardener

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

	201 Ct Zuposii C Com Cts/personal protection
· Additio	nal information about design of technical facilities: No further data; see item 7.
· 8.1 Con	trol parameters
· Ingredi	ents with limit values that require monitoring at the workplace:
1330-20	-7 Xylene (mix)
L	nort-term value: 441 mg/m³, 100 ppm ong-term value: 220 mg/m³, 50 ppm k; BMGV
100-41-	4 ethylbenzene
	nort-term value: 552 mg/m³, 125 ppm ong-term value: 441 mg/m³, 100 ppm k
123-86-	4 Butyl ethanoate
	nort-term value: 966 mg/m³, 200 ppm ong-term value: 724 mg/m³, 150 ppm
71-36-3	butanol
WEL S	hort-term value: 154 mg/m³, 50 ppm k
	(Contd. on page 4)

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K RS Non-Isocyante Hardener

(Contd. of page 3)

· Ingredients with biological limit values:

1330-20-7 Xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: When spraying the product, use a respiratory protective device.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and	chemical properties	
 9.1 Information on basic physica General Information Appearance: 	l and chemical properties	
Form:	Liquid	
Colour:	Clear	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	118 °C	
· Flash point:	25 °C	
		(Contd. on page 5

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K RS Non-Isocyanate Hardener

(Contd. of page 4)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	$1.006 \ g/cm^3$
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	NOT MISCIBLE
· Partition coefficient (n-octanol/wa	t ter): Not determined.
· Viscosity:	
Dynamic at 20 °C:	1600 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	41.8 %
Solids content:	58.2 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC3	0 values	relevant for	classification:

1330-20-7 Xylene (mix)

Oral		8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalati	ve LC50/4 h	6350 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

(Contd. on page 6)

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K RS Non-Isocyanate Hardener

(Contd. of page 5)

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECT	ION 14: Transport information	
	l-Number MDG, IATA	UN1263
· 14.2 UN · ADR · IMDG,	proper shipping name IATA	1263 PAINT RELATED MATERIAL (not viscous) PAINT RELATED MATERIAL
· 14.3 Tro	insport hazard class(es)	
· ADR, I	MDG, IATA	
· Class		3 Flammable liquids.
\cdot Label		3
	cking group MDG, IATA	III
	vironmental hazards: pollutant:	No
· 14.6 Sp	ecial precautions for user	Warning: Flammable liquids.
		(Contd. on page 7

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K RS Non-Isocyanate Hardener

(Contd. of page 6)

	(Conta. or pag
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
· 14.7 Transport in bulk according to An MARPOL73/78 and the IBC Code	nex II of
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
• • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN1263, PAINT RELATED MATERIAL (not viscous), III
or niouvicquium.	•

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	41.8

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing MSDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 8)

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K RS Non-Isocyanate Hardener

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(Contd. of page 7)

Printing date 01/08/2016 Revision: 01/08/2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

For professional use only

- · 1.1 Product identifier For professional use only
- · Trade name: 2K SR Non-Isocyanate Clearcoat
- · Article number: T252
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture Surface Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

TECHNICO SURFACE COATINGS LIMITED UNIT 14 BLYTHE PARK, SANDON ROAD CRESSWELL, STOKE ON TRENT STAFFORDSHIRE. ST11 9RD. TEL: +44 (0)1782 397400

EMAIL: <u>info@technicouk.com</u>

- · Further information obtainable from: Technico Office
- · 1.4 Emergency telephone number: +44 (0)1782 397400 (Business hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008





GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R10-67: Flammable. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotising effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

1330-20-7 | Xylene (mix)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K SR Non-Isocyanate Clearcoat

(Contd. of page 1)

- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard-determining components of labelling:

Butyl ethanoate

· Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

		e of substances listea below with nonnazaraous adaitions.	
· Danger	ous compone	ents:	
	3-86-4 S: 204-658-1	Butyl ethanoate R10-66-67 ~ Flam. Liq. 3, H226; ☑ STOT SE 3, H336	50-100%
	30-20-7 S: 215-535-7	Xylene (mix) (a) Xn R20/21; (a) Xi R38 R10	10-25%
		☐ Flam. Liq. 3, H226; ☐ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 10 EINECS)8-65-6 S: 203-603-9	2-methoxy-1-methylethyl acetate a Xi R36 R10	2.5-10%
		~ Flam. Liq. 3, H226; ~ Eye Irrit. 2, H319	

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K SR Non-Isocyanate Clearcoat

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep receptacles tightly sealed.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

123-86-4 Butyl ethanoate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

1330-20-7 *Xylene* (mix)

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

(Contd. on page 4)

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K SR Non-Isocyanate Clearcoat

(Contd. of page 3)

· Ingredients with biological limit values: 1330-20-7 Xylene (mix) BMGV | 650 mmol/mol creatinine | Medium: urine | Sampling time: post shift | Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Particulate cartridge filter type when LEV cannot be supplied
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and ch	gemical properties
· 9.1 Information on basic physical a · General Information	* *
· Appearance: Form: Colour: · Odour:	Fluid Clear Characteristic
· Odour threshold: · pH-value:	Not determined. Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 126°C
· Flash point:	24 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
	(Contd. on page 5

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K SR Non-Isocyanate Clearcoat

(Contd. of page 4)

	1 8 7
1.1 Vol %	
10.4 Vol %	
10.7 hPa	
0.956 g/cm^3	
Not determined.	
Not determined.	
Not determined.	
NOT MISCIBLE	
ater): Not determined.	
Not determined.	
Not determined.	
64.1 %	
35.9 %	
No further relevant information available.	
	10.4 Vol % 10.7 hPa 0.956 g/cm³ Not determined. Not determined. Not determined. NOT MISCIBLE ater): Not determined. Not determined. 10.4 Vol % 10.7 hPa 10.9 served. 10.9 serve

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 6)

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K SR Non-Isocyanate Clearcoat

(Contd. of page 5)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion
· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	1263 PAINT (not viscous)
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	30
· EMS Number:	F-E, <u>S-E</u>
· 14.7 Transport in bulk according to Ann	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per timer packaging: 50 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L

Printing date 01/08/2016 Revision: 01/08/2016

Trade name: 2K SR Non-Isocyanate Clearcoat

(Contd. of page 6)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN1263, PAINT (not viscous), 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	64.1

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R36 Irritating to eyes.

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

- · Department issuing MSDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3