



KAPCI
COATINGS

Page 1/8

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Kapci 805
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture .**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Kapci Coatings
Industrial Zone El - Raswa
Port Said
EGYPT
info@kapci.com
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +20 66 3770000

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS05

(Contd. on page 2)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

Trade name: Kapci 805

(Contd. of page 1)

• **Signal word** *Danger*

• **Hazard-determining components of labelling:**

butan-1-ol

• **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

• **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

• **Chemical characterisation: Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≤ 2.5%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	≤ 2.5%

• **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• **Description of first aid measures**

• **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

Trade name: Kapci 805

(Contd. of page 2)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

Trade name: Kapci 805

(Contd. of page 3)

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

71-36-3 butan-1-ol

WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk
-----	--

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

· **Ingredients with biological limit values:**

1330-20-7 xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

Trade name: Kapci 805

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:	Fluid
Colour:	According to product specification
• Odour:	Characteristic
• Odour threshold:	Not determined.

• pH-value:	Not determined.
-------------	-----------------

• **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C

• Flash point:	13 °C
----------------	-------

• Flammability (solid, gaseous):	Not applicable.
----------------------------------	-----------------

• Ignition temperature:	340 °C
-------------------------	--------

• Decomposition temperature:	Not determined.
------------------------------	-----------------

• Self-igniting:	Product is not selfigniting.
------------------	------------------------------

• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
------------------------	---

• **Explosion limits:**

Lower:	1.1 Vol %
Upper:	12.0 Vol %

• Vapour pressure at 20 °C:	43 hPa
-----------------------------	--------

• Density:	Not determined.
------------	-----------------

• Relative density	Not determined.
--------------------	-----------------

• Vapour density	Not determined.
------------------	-----------------

• Evaporation rate	Not determined.
--------------------	-----------------

• **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

• Partition coefficient (n-octanol/water):	Not determined.
--	-----------------

• **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

• **Solvent content:**

Organic solvents:	35.0 %
-------------------	--------

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

Trade name: Kapci 805

(Contd. of page 5)

VOC (EC)	35.00 %
Solids content:	65.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

Trade name: Kapci 805

· **Other adverse effects** No further relevant information available.

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1263
· ADR, IMDG, IATA	
· UN proper shipping name	1263 PAINT RELATED MATERIAL
· ADR	PAINT RELATED MATERIAL
· IMDG, IATA	
· Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	II
· ADR, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 8)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 24.06.2015

Trade name: Kapci 805

(Contd. of page 7)

· **UN "Model Regulation":**

UN1263, PAINT RELATED MATERIAL, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- **Department issuing MSDS:** Product safety department

- **Contact:** Mr. Rashad

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3



KAPCI
COATINGS

Page 1/8

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Kapci 806
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture .**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Kapci Coatings
Industrial Zone El - Raswa
Port Said
EGYPT
info@kapci.com
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +20 66 3770000

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS05

(Contd. on page 2)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

Trade name: Kapci 806

(Contd. of page 1)

- **Signal word** *Danger*

- **Hazard-determining components of labelling:**

butanol

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 78-83-1 EINECS: 201-148-0	butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-10%
CAS: 78-93-3 EINECS: 201-159-0	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

Trade name: Kapci 806

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

Trade name: Kapci 806

(Contd. of page 3)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

78-83-1 butanol

WEL Short-term value: 231 mg/m³, 75 ppm
Long-term value: 154 mg/m³, 50 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
Sk, BMGV

· **Ingredients with biological limit values:**

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

(Contd. on page 5)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

Trade name: Kapci 806

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:	Fluid
Colour:	According to product specification
• Odour:	Characteristic
• Odour threshold:	Not determined.

• pH-value:	Not determined.
-------------	-----------------

• **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C

• Flash point:	13 °C
----------------	-------

• Flammability (solid, gaseous):	Not applicable.
----------------------------------	-----------------

• Ignition temperature:	390 °C
-------------------------	--------

• Decomposition temperature:	Not determined.
------------------------------	-----------------

• Self-igniting:	Product is not selfigniting.
------------------	------------------------------

• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
------------------------	---

• **Explosion limits:**

Lower:	1.1 Vol %
Upper:	12.0 Vol %

• Vapour pressure at 20 °C:	43 hPa
-----------------------------	--------

• Density:	Not determined.
------------	-----------------

• Relative density	Not determined.
--------------------	-----------------

• Vapour density	Not determined.
------------------	-----------------

• Evaporation rate	Not determined.
--------------------	-----------------

• **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

• Partition coefficient (n-octanol/water):	Not determined.
--	-----------------

• **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

• **Solvent content:**

Organic solvents:	32.5 %
-------------------	--------

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

Trade name: Kapci 806

(Contd. of page 5)

VOC (EC)	32.50 %
Solids content:	67.5 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

Trade name: Kapci 806

· **Other adverse effects** No further relevant information available.

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1263
· ADR, IMDG, IATA	
· UN proper shipping name	1263 PAINT RELATED MATERIAL
· ADR	PAINT RELATED MATERIAL
· IMDG, IATA	
· Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	II
· ADR, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2015

Revision: 05.07.2015

Trade name: Kapci 806

(Contd. of page 7)

· **UN "Model Regulation":**

UN1263, PAINT RELATED MATERIAL, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

- **Department issuing MSDS:** Product safety department

- **Contact:** Mr. Rashad

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids, Hazard Category 2
 Flam. Liq. 3: Flammable liquids, Hazard Category 3
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

GB